



# Allied Full Synthetic DXP dexos1™ Motor Oil

*The ultimate in oil technology and utilizes the latest advanced synthetic hydrocarbon base stocks to exceed tough U.S. standards for an outstanding level of advanced protection and performance in today's harder working, hotter running gasoline engines.*

Allied Full Synthetic DXP dexos1™ Motor Oils are manufactured with 100% virgin high viscosity index premium quality, synthetically hydroprocessed North American base stocks with superior thermal and oxidative stability and excellent high and low temperature properties enhancing volatility and low temperature viscosity performance.

They also contain specially designed, technologically advanced, rigorously tested and field proven additive system. They provide superior wear protection, excellent deposit control, reduced starting friction, outstanding protection against viscosity and thermal breakdown, and improved fuel economy.

These high quality formulas minimize cold weather oil thickening, which greatly reduces battery drain and engine wear, even at subzero start ups.

All Allied products are formulated to meet, or exceed, all relevant industry standards. The chart below highlights the key protection and performance features and benefits provided by our **Allied Full Synthetic DXP dexos1™ Motor Oil.**

## FEATURES

Exclusively utilizes application specific 100% virgin base oils including high quality Synthetic base stocks

Utilizes a technologically advanced, API SM, ILSAC GF-5 passenger car detergent inhibitor additive system

## BENEFITS

- Exceptional thermal and oxidative stability prevents deposit formation and fluid thickening
- Ensures rapid oil circulation and engine protection on start-up even at very low temperatures
- Low coefficient of friction ensure maximum delivery of engine power
- Improved protection against viscosity and thermal breakdown at high temperatures
- Lower volatility reduces oil consumption
- Excellent Shear Stability maintains viscosity throughout service life
- Severe duty-Extreme temperatures-trailer towing
- High detergency and superior dispersancy keeps engine clean
- Exceptional anti-wear properties ensure long engine life
- Excellent protection against rust and corrosion
- Friction reducing technology resulting in improvement in fuel economy
- Meets or exceeds GM dexos1™ specifications for world wide requirements for all GM automotive gasoline engines currently in use



To find out more about our products and services, contact us at: (402) 344-4343 or visit [www.alliedoil.com](http://www.alliedoil.com)



# Allied Full Synthetic DXP dexos1™ Motor Oil

## Typical Properties:

PROPERTY	METHOD	0W-20 Full Syn	5W-30 Full Syn
Gravity, °API	ASTM D287	35.36	34.15
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.848	0.8542
Viscosity @ 40°C cSt	ASTM D445	43	63.95
Viscosity @ 100°C cSt	ASTM D445	8.272	10.93
Viscosity Index	ASTM D2270	171	163
Pour Point °C (°F)	ASTM D5950	-45°C (-49°F)	-45°C (-49°F)
Cold Cranking Simulator at (°C), cP	ASTM D5293	5300 (-35)	5100 (-30)
High Shear Vis at 100°C, cP	ASTM D 6616	5.7	7.15
High Shear Vis at 150°C, cP	ASTM D4683	2.63	3.2
Noack Volatility, % loss	ASTM D 5800	12.6	10.5
Color	ASTM D 1500	2.5	2.5
Zinc, wt. %	ASTM D 5185	0.085	0.085
Phosphorus, wt. %	ASTM D 5185	0.079	0.079
Calcium, wt. %	ASTM D 5185	0.214	0.214
Sulfur, wt. %	ASTM D 4951	0.306	0.252
Boron, wt. %	ASTM D 5185	0.023	0.023
Molybdenum, wt. %	ASTM D 5185	0.0079	0.0079
Sulfated Ash, wt. %	ASTM D 874	0.92	0.92
Nitrogen, wt. %	ASTM D 4629	0.102	0.102
Pumping Viscosity at (°C), cP	ASTM D4684	21,000 (-40)	18,400 (-35)
CLAIMS INFORMATION		0W-20 Full Syn	5W-30 Full Syn
		API SN	API SN
		API SM	API SM
		API SL	API SL
		ILSAC GF-5	ILSAC GF-5
		ILSAC GF-4	ILSAC GF-4
			M2C946-A
			GM 6094M

**ALWAYS CONSULT OWNERS MANUAL  
FOR CORRECT VISCOSITY GRADE**

Due to our goal of continuous improvement and commitment to keep pace with changing requirements, the information contained in this product sheet is subject to formulation changes without notification. Check with your Allied sales representative to make sure you have the most up-to-date product sheet. The version to reference is located in the right hand corner of this product sheet.

### ALLIED OIL & TIRE COMPANY Branch Locations:

**OMAHA, NE** • 2209 S. 24th Street • (402) 344-4343  
**KANSAS CITY, MO** • 5150 East Front Street • (816) 474-8040  
**DES MOINES, IA** • 5201 N.E. 15th Street • (515) 262-9381  
**JOPLIN, MO** • I-44 & Hwy 43 • (417) 623-4771  
**SIOUX FALLS, SD** • I-90, Exit 402 • (605) 332-3352  
**WICHITA, KS** • 3619 North Poplar Street • (316) 616-6300