



XTR Fleet API CI-4

XTR Fleet API CI-4 15W-40 and 10W-30 Diesel Engine Oils

High Quality Base Oils and High Performance Additives Keep Engines Well Protected

Allied XTR Fleet API CI-4 SAE 15W-40 and SAE 10W-30 Diesel Engine Oils are specially formulated to meet the demanding requirements of older engines developed before 2004 emissions regulations and traditional diesel and gasoline engines that specify a CI-4 oil.

These lubricants are built with 100 percent virgin high-viscosity index paraffinic base stocks; a technologically advanced and field proven detergent/dispersant inhibitor additive system; shear-stable viscosity modifiers; and antioxidants. XTR Fleet API CI-4 15W-40 and 10W-30 Diesel Engine Oils deliver outstanding performance, protection and value.

These oils offer soot induced wear control and viscosity control, excellent viscosity retention, superior thermal and oxidative stability, and outstanding low and high temperature properties.

You can rely on XTR Fleet API CI-4 15W-40 and 10W-30 Diesel Engine Oils in all seasons, under all operating conditions to maximize and prolong engine life.

Performance Attribute

Performance Benefit

Soot Dispersancy

Keeps soot suspended in the oil for reduced wear and cleaner engines even with longer drain intervals and increased soot loading.

High Detergency

Reduces deposit formation for cleaner components and cleaner engines and increased protection against rust and corrosion.

Superior Thermal and Oxidative Stability

Prevents deposit formation and fluid thickening.

Lower Volatility

Reduces oil consumption, especially in extended drain service.

Shear-Stable Viscosity Improvers

Maintains excellent oil flow and viscosity for outstanding wear protection under all operating conditions.



ALLIED
OIL & SUPPLY, INC.

To find out more about our products and services, contact us at: (800) 333-3717 or visit www.alliedoil.com



XTR Fleet API CI-4 15W-40 and 10W-30 Diesel Engine Oils

Recommended for:

On- and off-highway diesel applications and heavy-duty gasoline fleets operating under all service conditions, including heavy-duty trucking, construction, mining, and farm equipment.

Specifications/Approvals:

Meets or exceeds all relevant industry standards, including: API categories CI-4, CH-4, CG-4, CF and SL

- Mack EO-M Plus
- Caterpillar ECF-1-a
- Cummins CES 20078, 20077, 20076
- Detroit Diesel Series: 30, 40, 50, 55, 60*
- Ford, Ford Truck, New Holland
- John Deere
- Allison C-4*
- Deutz Diesel*
- Komatsu
- Mercedes Benz p.228.3
- Volvo VDS-3, VDS-2
- Global DHD-1
- ACEA E5*

*15W-40 only

Typical Properties:

PROPERTY	METHOD	15W-40	10W-30
KV @ 100°C, cSt	ASTM D-445	15.2	11.8
KV @ 40°C, cSt	ASTM D-445	116	77.6
Viscosity Index	ASTM D-2270	137	145
HTHS Viscosity @ 150°C, cP	ASTM D-4683	4.1	3.5
MRV @ -25°C, cP	ASTM D-4684	22,100	
MRV @ -30°C, cP	ASTM D-4684		23,230
CCS Viscosity @ -20°C, cP	ASTM D-5293	6,847	
CCS Viscosity @ -25°C, cP	ASTM D-5293		6,207
Sulfated Ash, wt. %	ASTM D-874	1.22	1.22
Total Base Number	ASTM D-2896	10	10

