

Description

DEXVI MERC LV MV FULL SYN ATF

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	35.6
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8468
Flash Point, °C	ASTM D92	220
Flash Point, °F	ASTM D92	428
Viscosity @ 40°C, cSt	ASTM D445	28.56
Viscosity @ 100°C, cSt	ASTM D445	5.797
Viscosity Index	ASTM D2270	151
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	10,300
Color	ASTM D1500	Red

Claims Information

Allison C-3	Suitable for Use
Allison C-4	Suitable for Use
Audi 5 HP LT71141, G 052 162-A1/A2, G 052 025 A2, 053 025 A2, 060 162, 055 540, 052 990, 052 055	Suitable for Use
Bentley PY112995PA	Suitable for Use
BMW JWS 3309, LA2634, 7045E, LT71141, ETL 8072B, ZF 5HP18FL, 19FL, 5HP24, 5HP30,	Suitable for Use
Bosch TE-ML 09	Suitable for Use
CAT TO-2	Suitable For Use
Chrysler 05127382AA, 68043742AA, 68157995AA, 68157995AB, 68171866AA	Suitable for Use
Chrysler 8 and 9 speed transmissions, Mopar 8 & 9 fluid 68218925AA	Suitable for Use
Chrysler AS68RC, AS69RC (T-IV), Diamond SP-III	Suitable for Use
Daewoo LT 71141	Suitable for Use
Daihatsu AMMIX ATF D-II, D-III SP	Suitable for Use
Dexron III G/H, Dexron II D/E, Dexron, AW1	Suitable for Use
Dexron VI	Approvable by Brand
Esso LT 71141	Suitable for Use
Fiat T-VI, JWS 3309	Suitable for Use
Ford M2C166H, 138CJ, 922A1, 924A, JWS 3309, XT-2-QDX, XT-2-QSM, Ford FNR5, (Mazda M5, XT-9-QMM5), XL-12, Ford M2C138-CJ, XT8QAW	Suitable for Use
Ford Mercon LV (FF-WSS M2C938A/SF, XT-10-QLV)	Approvable by Brand
Fuchs 3353	Suitable for Use
FUSO ATF-II, SPIII, A4	Suitable for Use
GM, GMC, Opel, Saturn, 88863400, 88863401, T-IV, JWS 3309, 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466, 88900925, 9986195 (Aisin AW), AS69RC,	Suitable for Use
GMN 10060	Meets Requirements
Hino Blue Ribbon ATF	Suitable For Use
Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	Suitable for Use
Hyundai/Kia SP-IV, SP-IV M, SPH-IV, SP-IV RR, SP-III, Dex-II/SP-II, JWS 3314, 9683, 04000090SG, NUMM040 CH20 Red-1	Suitable for Use
IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	Suitable for Use
ISUZU BESCO ATF-II, III, Isuzu SCS, ATF-III, ATF SP, 08200-9001	Suitable For Use
Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238, K17, 20292, 8432, 02JDE26444, WSS-M2C922A1,	Suitable for Use
JASO 1A-LV	Suitable for Use
JWS 3309, Any 3309	Suitable for Use
JWS 3324	Suitable for Use
Land Rover LR023288	Suitable for Use
Lexus JWS 3309	Suitable for Use
MAN 339A, 339 Type V2, V1, Z2, Z1	Suitable for Use

Claims Information

Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317, T-IV	Suitable for Use
MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9	Suitable for Use
Mini Cooper T-IV, MINI P/N 83 22 0 402 413	Suitable for Use
Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF-MA1, PA	Suitable for Use
NAG-1 (Chrysler, Jeep, Cherokee)	Suitable for Use
Nissan Matic C, D, J, K, S, 402	Suitable for Use
Peugeot/Citreon ZF 4HP20, Renault Samsung DPO/AL4, SAAB 93 160 393, MB ZF 4HP20, Matic D2, SATF-D, Z 000169756, (PSA) AL4 Auto gearbox oil (#9730.AE)	Suitable for Use
Porsche P/N 999 917 547 00 (A2), ZF 5HP16FL, 19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 000 043 205 28	Suitable for Use
SAAB T-IV, 3309, 93 165 147, 93 160 393	Suitable for Use
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466, 88900925, 93160393,	Suitable for Use
Ssang yong DSIH 5M-66	Suitable for Use
Scion	Suitable for Use
Shell L 12108, 3403 M115, LA2634, ETL-8072B	Suitable for Use
Subaru ATF 5AT, Dex II, AT OIL 5D06, ATF, ATF HP	Suitable for Use
Suzuki ATF 2326, 2384K, JWS 3309, 3314, AT OIL 5D06, ATF 2326, ATF 2384K, 3317	Suitable for Use
Texaco 7045-E, 8072B, N402	Suitable for Use
Toyota D-II, D-III, Hybrid, T-II, T-III, T-IV, WS	Suitable for Use
Type A	Suitable for Use
Vickers M-2950-S, I-286-S	Suitable for Use
Voith 55.6335 (G607), Svc Bltn #013 and #118	Suitable for Use
Volvo 97325, 97335, CE 97340, 1161521, 1161621, 1161540, 1161640, 31256774, 31256675	Suitable for Use
Volvo P/N 1161540-8	Suitable for Use
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Suitable for Use
VW 5 HP ZF5 HP 30, 18FL, 30, 19FL, 24A, G-055-025 A2, G-055-540, G-055-162 (ZF Lifeguardfluid 5), G-055-162-A2, -A6 (ZF Lifeguardfluid 6 Plus), G-060-162 (ZF Lifeguardfluid 8), G US 000 162, TL 521 62, TL 521 62, TL 52540 A, VW G 052 162, 052 162 A1 A2 A6, 099, VW TL52162 (LT71141)	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-389	Suitable for Use
ZF all 3 & 4 speed trans., 8 speed trans., 9 speed trans., ZF TE-ML 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 14C, 16L, 17C, 21L	Suitable for Use