

Universal Yellow Coolant 50/50

Multi-Vehicle Extended Life Antifreeze/Coolant

Specifications, Approvals & Recommendations

- ASTM D3306

For a full listing of equipment approvals and recommendations, please consult your local representative.

Typical Physical Characteristics

Properties		Method	Universal Yellow Coolant 50/50
Color		Visual	Yellow
Specific Gravity	60/60°F	ASTM D1122	1.06-1.09
pH, 50% Solution		ASTM D1287	8.3
Freeze Pt., 50/50 Dilution	°C (°F)	ASTM D1177	-36.7 (-34)
Boiling Point	°C (°F)	ASTM D1120	+108 (+226)
Reserve Alkalinity	ml 0.1N HCL	ASTM D1121	1.6

These characteristics are typical of current production.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your local representative.

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.