



# SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Kubota® SAE 15W-40 Diesel Engine Oil

Product code : 791479

|   |   |
|---|---|
| <b>Details of the supplier of the safety data sheet</b><br>Valvoline LLC<br>100 Valvoline Way<br>Lexington, KY 40509<br>United States of America (USA)<br>1-800-TEAMVAL (1-800-832-6825)<br><br>SDS@valvoline.com | <b>Emergency telephone number</b><br>1-800-VALVOLINE (1-800-825-8654)<br><br><b>Regulatory Information Number</b><br>1-800-TEAMVAL (1-800-832-6825)<br><br><b>Product Information</b><br>1-800-TEAMVAL (1-800-832-6825) |
|---|---|

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Not a hazardous substance or mixture.

### GHS label elements

Not a hazardous substance or mixture.

### Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:  
10.7668 %

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components

| Chemical name  | CAS-No.    | Classification                           | Concentration (%) |
|--|------------|--|-------------------|
| DISTILLATES (PETROLEUM),<br>HYDROTREATED HEAVY<br>PARAFFINIC | 64742-54-7 | Not a hazardous<br>substance or mixture. | >=80.00 - < 90.00 |



# SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

|  |            |  |                 |
|--|------------|--|-----------------|
| DISTILLATES (PETROLEUM),<br>SOLVENT-DEWAXED HEAVY<br>PARAFFINIC                                    | 64742-65-0 | Asp. Tox. 1; H304                          | >=1.50 - < 5.00 |
| Phosphorodithioic acid, mixed<br>O,O-bis(2-ethylhexyl and iso-Bu<br>and iso-Pr) esters, zinc salts | 85940-28-9 | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319 | >=1.50 - < 5.00 |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.  
Show this safety data sheet to the doctor in attendance.  
Move out of dangerous area.
- If inhaled : If symptoms persist, call a physician.  
If unconscious, place in recovery position and seek medical  
advice.
- In case of skin contact : Wash contaminated clothing before re-use.  
If on skin, rinse well with water.  
Remove contaminated clothing. If irritation develops, get  
medical attention.
- In case of eye contact : Protect unharmed eye.  
Remove contact lenses.  
Immediately flush eye(s) with plenty of water.
- If swallowed : If symptoms persist, call a physician.  
Never give anything by mouth to an unconscious person.  
Do not give milk or alcoholic beverages.  
Obtain medical attention.
- Most important symptoms  
and effects, both acute and  
delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local  
circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)



# SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

Dry chemical

Unsuitable extinguishing media

: High volume water jet

Specific hazards during firefighting

: Do not allow run-off from fire fighting to enter drains or water courses.  
If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

Hazardous combustion products

: carbon dioxide and carbon monoxide  
Nitrogen oxides (NOx)

Specific extinguishing methods

: Product is compatible with standard fire-fighting agents.

Further information

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters

: In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.  
Ensure adequate ventilation.  
Use personal protective equipment.

Environmental precautions

: If the product contaminates rivers and lakes or drains inform respective authorities.  
Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

Other information

: Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

- Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid contact with skin and eyes.  
Avoid exposure - obtain special instructions before use.  
Container hazardous when empty.  
Do not smoke.  
Do not breathe vapours/dust.
- Conditions for safe storage : Observe label precautions.  
Keep container tightly closed in a dry and well-ventilated place.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

| Components  | CAS-No.    | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---|------------|-------------------------------|--|-----------|
| DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC | 64742-65-0 | TWA                           | 5 mg/m3 Mist                                   | OSHA Z-1  |
|   |            | TWA                           | 5 mg/m3 Inhalable particulate matter           | ACGIH     |
|   |            | TWA                           | 5 mg/m3 Mist                                   | OSHA P0   |
|   |            | TWA                           | 5 mg/m3 Mist                                   | NIOSH REL |
|   |            | ST                            | 10 mg/m3 Mist                                  | NIOSH REL |
|   |            | PEL                           | 5 mg/m3 particulate                            | CAL PEL   |
| HYDROTREATED LIGHT PARAFFINIC DISTILLATE                  | 64742-55-8 | TWA                           | 5 mg/m3 Mist                                   | OSHA Z-1  |
|   |            | TWA                           | 5 mg/m3 Inhalable particulate matter           | ACGIH     |
|   |            | TWA                           | 5 mg/m3 Mist                                   | OSHA P0   |
|   |            | TWA                           | 5 mg/m3 Mist                                   | NIOSH REL |
|   |            | ST                            | 10 mg/m3 Mist                                  | NIOSH REL |



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

|  |  |     |                        |         |
|--|--|-----|------------------------|---------|
|  |  | PEL | 5 mg/m3<br>particulate | CAL PEL |
|--|--|-----|------------------------|---------|

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection  
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear resistant gloves (consult your safety equipment supplier).  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Safety shoes  
Impervious clothing  
Wear as appropriate:

Hygiene measures

: When using do not smoke.  
When using do not eat or drink.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

---

|  |   |  |
|--|---|--|
| Colour   | : | amber  |
| Odour  | : | hydrocarbon-like   |
| Odour Threshold                                  | : | No data available  |
| pH   | : | No data available  |
| Melting point/freezing point                     | : | No data available  |
| Boiling point/boiling range                      | : | No data available  |
| Flash point                                      | : | > 390 °F / > 199 °C<br>Method: Cleveland open cup                |
| Evaporation rate                                 | : | No data available  |
| Flammability (solid, gas)                        | : | No data available  |
| Self-ignition                                    | : | No data available  |
| Upper explosion limit / Upper flammability limit | : | 6 %(V)<br>Calculated Explosive Limit                             |
| Lower explosion limit / Lower flammability limit | : | 1 %(V)<br>Calculated Explosive Limit                             |
| Vapour pressure                                  | : | 0.0133333 hPa (70.00 °F / 21.11 °C)<br>Calculated Vapor Pressure |
| Relative vapour density                          | : | No data available  |
| Relative density                                 | : | No data available  |
| Density  | : | 0.880 g/cm <sup>3</sup> (60.1 °F / 15.6 °C)                      |
| Solubility(ies)                                  |   |  |
| Water solubility                                 | : | negligible   |
| Solubility in other solvents                     | : | No data available  |
| Partition coefficient: n-octanol/water           | : | No data available  |
| Decomposition temperature                        | : | No data available  |



# SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : ca. 112 mm<sup>2</sup>/s (104 °F / 40 °C)  
Oxidizing properties : No data available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.  
Chemical stability : Stable under recommended storage conditions.  
Possibility of hazardous reactions : Product will not undergo hazardous polymerization.  
Conditions to avoid : excessive heat  
Incompatible materials : Acids  
Strong oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

### **DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:**

Acute oral toxicity : LD50 (Rat): 2,570 - 3,700 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : May cause skin irritation in susceptible persons.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:**

Species : Rabbit  
Result : Irritating to skin.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Causes serious eye irritation.  
Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation





**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:**

Species : Rabbit  
Result : Irritating to eyes.

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:**

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

**Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Not classified based on available information.



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

Long-term (chronic) aquatic hazard : Not classified based on available information.

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:  
Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 5.4 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF

Toxicity to algae : (Selenastrum capricornutum (green algae)): 2.1 mg/l  
End point: Growth inhibition  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF

**Persistence and degradability**

**Components:**

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:  
Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1.5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
Remarks: Information given is based on data obtained from similar substances.

No data available

**Bioaccumulative potential**

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:  
Partition coefficient: n-octanol/water : log Pow: Expected > 7

Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts:  
Partition coefficient: n-octanol/water : log Pow: 8.8  
Remarks: QSAR

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

---

|                                   |   |
|-----------------------------------|---|
| Regulation                        | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  |
| Remarks                           | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : No data available   |

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

|                        |  |
|------------------------|--|
| General advice         | : Dispose of in accordance with all applicable local, state and federal regulations.<br><br>Send to a licensed waste management company.<br>Do not contaminate ponds, waterways or ditches with chemical or used container.<br>Do not dispose of waste into sewer. |
| Contaminated packaging | : Do not re-use empty containers.<br>Empty containers should be taken to an approved waste handling site for recycling or disposal.<br>Dispose of as unused product.<br>Empty remaining contents.  |

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**CFR\_ROAD**

Not regulated as a dangerous good



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|   |            |              |
|---|------------|--------------|
| Phosphorodithioi<br>c acid, mixed<br>O,O-bis(2-<br>ethylhexyl and<br>iso-Bu and iso-<br>Pr) esters, zinc<br>salts | 85940-28-9 | >= 1 - < 5 % |
|---|------------|--------------|

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any priority pollutants related to the U.S. Clean Water Act

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307



**SAFETY DATA SHEET**  
Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

Phosphorodithioic acid, 85940-28-9  $\geq 1 - < 5 \%$   
mixed O,O-bis(2-  
ethylhexyl and iso-Bu  
and iso-Pr) esters, zinc  
salts

**The components of this product are reported in the following inventories:**

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

**TSCA list**

No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

---

**SECTION 16. OTHER INFORMATION**

**Further information**

Internal information : R0171784

**NFPA:**

**HMIS III:**



# SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

|  |  |               |          |                     |          |                        |          |
|--|--|---------------|----------|---------------------|----------|------------------------|----------|
| <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p> | <table border="1"><tr><td><b>HEALTH</b></td><td><b>0</b></td></tr><tr><td><b>FLAMMABILITY</b></td><td><b>1</b></td></tr><tr><td><b>PHYSICAL HAZARD</b></td><td><b>0</b></td></tr></table> <p>0 = not significant, 1 =Slight,<br/>2 = Moderate, 3 = High<br/>4 = Extreme, * = Chronic</p> | <b>HEALTH</b> | <b>0</b> | <b>FLAMMABILITY</b> | <b>1</b> | <b>PHYSICAL HAZARD</b> | <b>0</b> |
| <b>HEALTH</b>  | <b>0</b>   |               |          |                     |          |                        |          |
| <b>FLAMMABILITY</b>  | <b>1</b>   |               |          |                     |          |                        |          |
| <b>PHYSICAL HAZARD</b>   | <b>0</b>   |               |          |                     |          |                        |          |

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

### Full text of H-Statements

- |      |   |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation.                       |
| H319 | Causes serious eye irritation.                |

### Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.



## SAFETY DATA SHEET

Kubota® SAE 15W-40 Diesel Engine Oil

Version: 2.7

Revision Date: 06/15/2021

Print Date:  
07/12/2022

---

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System