

Description

ALLIED SYNTAX GO FS 75W90 16

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	32.52
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.8627
Flash Point, °C	ASTM D92	232
Flash Point, °F	ASTM D92	450
Viscosity at 40°C, cSt	ASTM D445	109.3
Viscosity at 100°C, cSt	ASTM D445	16.15
Viscosity Index	ASTM D2270	159
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	135,000
Color	ASTM D1500	1
Phosphorus, wt. %	ASTM D5185	0.047
Sulfur, wt. %	ASTM D4951	1.6

Claims Information

AGMA 9005-E02, 250.03, 250.04, 251.02, No. 4	Meets Requirements
AIST/US Steel 224	Meets Requirements
API GL-5	Meets Requirements
ArvinMeritor 076-N, E	Meets Requirements
Ford M2C108C	Meets Requirements
GM 9986115	Suitable for Use
Limited Slip	Suitable for Use
Mack GO-J, GO-H, GO-G	Meets Requirements
MT-1	Meets Requirements
SAE J2360, MIL-2105E/F	Meets Requirements