

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: CASSIDA SILICONE FLUID

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating oil

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

FUCHS LUBRITECH GmbH
Werner-Heisenberg-Straße 1
67661 Kaiserslautern/Germany

US Distributor
Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426
(708) 333-8900
(800) 255-3924 24 hrs Emergency

Telephone:

+49 (0) 6301 3206-0

Fax:

+49 (0) 6301 3206-940

Contact Person:

FUCHS LUBRITECH GmbH - Product Safety Management

Telephone:

+49 (0) 6301 3206-0

Fax:

+49 (0) 6301 3206-940

E-mail:

reach@fuchs-lubritech.de

1.4 Emergency telephone number:

+49 (0) 6301 3206-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous and does not need to be labelled according to regulation (EU) no 1272/2008 (CLP).

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

not applicable

2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

Product name: CASSIDA SILICONE FLUID

3.1 Substances

General information:

Chemical name: Polydimethylsiloxane

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Product name: CASSIDA SILICONE FLUID

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures:** In case of spills, beware of slippery floors and surfaces.
- 6.2 Environmental Precautions:** Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
- 6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
- 7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed.
- 7.3 Specific end use(s):** No data available.
- Storage Class:** 10, Combustible liquids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Product name: CASSIDA SILICONE FLUID

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166) recommended during refilling.
Skin protection	
Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: ≥ 480 min Recommended thickness of the material: $\geq 0,38$ mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	Not known.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Colorless
Odor:	Odorless
Odor Threshold:	Value not relevant for classification
pH:	not applicable
Freezing point:	-50 °C
Boiling Point:	Value not relevant for classification
Flash Point:	> 300 °C (DIN EN ISO 2592)
Evaporation Rate:	Value not relevant for classification
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)–:	
Flammability Limit - Lower (%)–:	

Product name: CASSIDA SILICONE FLUID

Vapor pressure:	Value not relevant for classification
Vapor density (air=1):	Value not relevant for classification
Density:	0,98 g/cm ³ (15 °C) (DIN 51757)
Solubility(ies)	
Solubility in Water:	The product is insoluble in water.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Value not relevant for classification
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	350 mm ² /s (20 °C, DIN 51562)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification

9.2 Other information

Minimum ignition temperature:	> 450 °C (DIN 51794)
--------------------------------------	----------------------

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

OralPolydimethylsiloxan LD 50 (Rat): > 5.001 mg/kg

Dermal

No data available.

Inhalation

No data available.

Skin Corrosion/Irritation:

 Polydimethylsiloxan (Rabbit):
 Not irritant.

Product name: CASSIDA SILICONE FLUID

Serious Eye Damage/Eye Irritation:
Polydimethylsiloxan (Rabbit):
Not irritant.

Respiratory or Skin Sensitization:
No data available.

Germ Cell Mutagenicity

In vitro
No data available.

In vivo
No data available.

Carcinogenicity
No data available.

Reproductive toxicity
No data available.

Specific Target Organ Toxicity - Single Exposure
No data available.

Specific Target Organ Toxicity - Repeated Exposure
No data available.

Aspiration Hazard
No data available.

Other Adverse Effects: No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Fish
No data available.

Aquatic Invertebrates
No data available.

Chronic Toxicity

Fish
No data available.

Aquatic Invertebrates
No data available.

Product name: CASSIDA SILICONE FLUID

Toxicity to Aquatic Plants

No data available.

12.2 Persistence and Degradability

Biodegradation

No data available.

12.3 Bioaccumulative Potential

No data available.

12.4 Mobility in Soil:

No data available.

12.5 Results of PBT and vPvB assessment:

Polydimethylsiloxane

Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria.

12.6 Other Adverse Effects:

No data available.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Dispose in accordance with all applicable regulations.

Disposal methods:

Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

European Waste Codes

13 02 08*: other engine, gear and lubricating oils

SECTION 14: Transport information

ADR/RID

- 14.1 UN Number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
 - Class: Non-dangerous goods
 - Label(s): —
 - Hazard No. (ADR): —
 - Tunnel restriction code: —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

Product name: CASSIDA SILICONE FLUID

ADN

14.1 UN Number: –
14.2 UN Proper Shipping Name: –
14.3 Transport Hazard Class(es)
Class: Non-dangerous goods
Label(s): –
14.3 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

IMDG

14.1 UN Number: –
14.2 UN Proper Shipping Name: –
14.3 Transport Hazard Class(es)
Class: Non-dangerous goods
Label(s): –
EmS No.: –
14.3 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

IATA

14.1 UN Number: –
14.2 Proper Shipping Name: –
14.3 Transport Hazard Class(es):
Class: Non-dangerous goods
Label(s): –
14.4 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Product name: CASSIDA SILICONE FLUID

Wording of the H-statements in section 2 and 3

none

Other information:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies. The classification results from the Conventional Method mentioned in regulation EU 1272/2008 (CLP).

Revision Date:

23.05.2016

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.