

Sturaco® 7098 LO

Friction modifier

DESCRIPTION

Sturaco 7098 LO is a friction modifier to supplement sulfur-phosphorous gear oil additives for limited-slip performance.

Sturaco 7098 LO has been specially modified to have a low odor content.

Sturaco 7098 LO is a balanced additive formulated for use in conjunction with various lubricants. Mil-L-2105D gear oil for limited-slip characteristics use 2% to 5%:

Manual transaxles	3% - 5%
Engine oil for noise reduction	1% - 2%
Universal tractor fluids	2% - 4%

FEATURES / BENEFITS

- Excellent anti-chatter properties
- Short term solution to wear caused by mechanical problems
- Approval for use by major automotive manufacturers

Sturaco 7098 LO should be stored at ambient temperatures. Should the product be subjected to temperatures below 20°C, it should be warmed to ambient before use.

DATA (TYPICAL VALUES)

Specific Gravity 15.6°C	0.92
Viscosity @ 100°C	9 to 10 cSt

HEALTH AND SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

CF 14.05 US



Houghton International Inc.
 Madison and Van Buren Aves.
 P. O. Box 930
 Valley Forge, PA 19482-0930

Phone: 610-666-4000
 Fax: 610-666-0174
 info@houghtonintl.com
 www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.