

SHIPMATE 4 STROKE MARINE ENGINE OIL

DESCRIPTION:

Shipmate 4-Stroke Marine Engine Oil SAE 30 is a heavy-duty premium engine oil specially formulated for high performance four stroke diesel and gasoline outboard and inboard marine engines. Shipmate 4-Stroke Marine Engine Oil is a proven engine lubricant designed for high output diesel and gasoline engines operating under severe marine service conditions. Trouble-free service in major engine manufacturers marine engines demonstrates the effectiveness of this product.

Shipmate 4-Stroke Marine Engine Oil SAE 30 is formulated with high quality base stocks and proven additive system with the proper balance of detergents and dispersants, anti-wear agents, multipurpose inhibitors and corrosion control additives.

APPLICATION:

Shipmate 4-Stroke Marine Engine Oil covers both diesel and gasoline inboard and outboard marine engines where a SAE 30 grade oil is recommended. It is formulated to meet or exceed a variety of specifications and engine manufacturers standards.

- API Service Categories as listed in the typical listing
- Newer and older four stroke diesel and gasoline engines calling for a SAE 30

FEATURES & BENEFITS:

Excellent high temperature lubrication performance maximizing engine life.

Mixed service for both gasoline and diesel marine engines reduces misapplications.

Superb deposit control demonstrating outstanding engine cleanliness in critical areas.

Prevents wear by providing stable viscosity at high temperature, high RPM conditions.

Improved oxidation and rust protection throughout the oil drain interval.

SHIPMATE 4 STROKE ENGINE OIL
Typical Properties

| | |
|------------------------------|---------------------------|
| SAE Viscosity Grade | 30 |
| API Service suitable for use | CI-4,CF-2, CF/SM,SL,SJ |
| Viscosity, cSt @ 40°C | 91.0 |
| @ 100°C | 11.5 |
| Viscosity Index | 114 |
| API Gravity/ lbs/gal | 29.5/7.32 |
| Pour Point, °F | 5 |
| Sulfated Ash, % wt. | <1.0 |
| TBN (D 2896) | 10 |

The typical properties listed reflect the general characteristics of the product and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY:

Used motor oil contains combustion by-products which may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact your Allied Sales Representative.

September 2022