

HD Pink



Description

ThermoPro® HD Pink 50/50 ready-to-use antifreeze/coolant is a fully formulated conventional antifreeze for use in heavy duty and light duty engines, including Caterpillar, Detroit Diesel and Cummins. The premier borate-based inhibitor package, with nitrite, provides superior protection against liner pitting, corrosion and scale formation. HD Pink is phosphate free and contains low levels of silicate.

Benefits

- Compatible for use in heavy duty and light duty applications
- Provides year round protection against liner pitting, corrosion and scale formation.
- Fully formulated ready-to-use formula eliminates mixing errors and water quality issues that harm engines
- Can be used when topping off without adding additional SCAs (supplemental coolant additives)

Formulated to meet specifications

ASTM D-3306	ASTM D-4985	ASTM D-6210
Case MS1710	Caterpillar	CID A-A 52624A
Cummins CES 14603	Detroit Diesel 7SE298	EMD M.I. 1748E
Freightliner 48-22880	GM 1825	GM 1899
John Deere 8650-5	Mack	Navistar
New Holland 9-86	Paccar	SAE 1941
TMC RP329	Volvo GM	Waukesha 4-1974D

Properties	Typical Values	Test Method
Specific Gravity, 68°F	1.052 - 1.084	ASTM D-1122
pH	10.2 - 10.8	ASTM D-1287
Foam (mil/sec)	100/3 max	ASTM D-1881
Total Water*, Wt. %	48% max	
Total Glycol, Wt. %	50% min	
Total Inhibitors, Wt. %	1% min	

*Deionized

Protection Chart

Concentration	50%
Boiling Point**	265°F
Freezing Point	-34°F

** Shown using a conventional 15 psi radiator cap.



1612 7th Street NW
Faribault, MN 55021
Tel 507.334.0442
Fax 507.334.0460
www.ETU-MN.com