

Description

Allied FS MV Low Vis ATF

| Inspection Information | Test Method | Typical Value |
|-----------------------------------|--------------------|----------------------|
| Gravity, °API | ASTM D287 | 35.6 |
| Specific Gravity at 60°F (15.6°C) | ASTM D4052 | 0.8468 |
| Flash Point, °C | ASTM D92 | 220 |
| Flash Point, °F | ASTM D92 | 428 |
| Viscosity at 40°C, cSt | ASTM D445 | 28.56 |
| Viscosity at 100°C, cSt | ASTM D445 | 5.797 |
| Viscosity Index | ASTM D2270 | 151 |
| Pour Point, °C (°F) | ASTM D5950 | -51°C (-60°F) |
| Brookfield Viscosity at -40°C, cP | ASTM D2983 | 10,300 |
| Color | ASTM D1500 | 3 |



| Claims Information | |
|--|---------------------|
| Allison C-3 | Suitable for Use |
| Allison C-4 | Suitable for Use |
| Audi 5 HP LT71141, G 052 162-A1/A2, G 052 025 A2, 053 025 A2, 060 162, 055 540 A2, 052 990, 052 055 | Suitable for Use |
| Bentley PY112995PA | Suitable for Use |
| BMW JWS 3309, LA2634, 7045E, LT71141, ETL 8072B, ZF 5HP18FL, 19FL, 5HP24, 5HP30, | Suitable for Use |
| Bosch TE-ML 09 | Suitable for Use |
| CAT TO-2 | Suitable For Use |
| Chrysler 05127382AA, 68043742AA, 68157995AA, 68157995AB, 68171866AA | Suitable for Use |
| Chrysler 8 and 9 speed transmissions, Mopar 8 & 9 fluid 68218925AA | Suitable for Use |
| Chrysler AS68RC, AS69RC (T-IV), Diamond SP-III | Suitable for Use |
| Daewoo LT 71141 | Suitable for Use |
| Daihatsu AMMIX ATF D-II, D-III SP | Suitable for Use |
| Dexron HP | Suitable for Use |
| Dexron III G/H, Dexron II D/E, Dexron, AW1 | Suitable for Use |
| Dexron VI | Approvable by Brand |
| Esso LT 71141 | Suitable for Use |
| Fiat T-VI, JWS 3309 | Suitable for Use |
| Ford M2C166H, 138CJ, 922A1, 924A, JWS 3309, XT-2-QDX, XT-2-QSM, Ford FNR5, (Mazda M5, XT-9-QMM5), XL-12, Ford M2C138-CJ, XT8QAW | Suitable for Use |
| Ford Mercon LV (FF-WSS M2C938A/SF, XT-10-QLV) | Approvable by Brand |
| Fuchs 3353 | Suitable for Use |
| FUSO ATF-II, SPIII, A4 | Suitable for Use |
| GM Autotrak II (Transfer Case Fluid) | Suitable for Use |
| GM, GMC, Opel, Saturn, 88863400, 88863401, T-IV, JWS 3309, 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466, 88900925, 9986195 (Aisin AW), AS69RC, | Suitable for Use |
| GMN 10060 | Meets Requirements |
| Hino Blue Ribbon ATF | Suitable For Use |
| Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1 | Suitable for Use |
| Hyundai/Kia SP-IV, SP-IV M, SPH-IV, SP-IV RR, SP-III, Dex-II/SP-II, JWS 3314, 9683, 04000090SG, NUMM040 CH20 Red-1 | Suitable for Use |
| IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085 | Suitable for Use |
| ISUZU BESCO ATF-II, III, Isuzu SCS, ATF-III, ATF SP, 08200-9001 | Suitable For Use |
| Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238, K17, 20292, 8432, 02JDE26444, WSS-M2C922A1, | Suitable for Use |
| JASO 1A-LV | Suitable for Use |
| JWS 3309, Any 3309 | Suitable for Use |
| JWS 3324 | Suitable for Use |
| Land Rover LR023288 | Suitable for Use |



Claims Information

| | |
|--|------------------|
| Lexus JWS 3309 | Suitable for Use |
| MAN 339A, 339 Type V2, V1, Z2, Z1 | Suitable for Use |
| Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317, T-IV | Suitable for Use |
| MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9 | Suitable for Use |
| Mini Cooper T-IV, MINI P/N 83 22 0 402 413 | Suitable for Use |
| Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF-MA1, PA | Suitable for Use |
| NAG-1 (Chrysler, Jeep, Cherokee) | Suitable for Use |
| Nissan Matic C, D, J, K, P, S, 402 | Suitable for Use |
| Peugeot/Citreon ZF 4HP20, Renault Samsung DPO/AL4, SAAB 93 160 393, MB ZF 4HP20, Matic D2, SATF-D, Z 000169756, (PSA) AL4 Auto gearbox oil (#9730.AE) | Suitable for Use |
| Porsche P/N 999 917 547 00 (A2), ZF 5HP16FL, 19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 000 043 205 28 | Suitable for Use |
| SAAB T-IV, 3309, 93 165 147, 93 160 393 | Suitable for Use |
| Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466, 88900925, 93160393, | Suitable for Use |
| Ssang yong DSIH 5M-66 | Suitable for Use |
| Scion | Suitable for Use |
| Shell L 12108, 3403 M115, LA2634, ETL-8072B | Suitable for Use |
| Shell M-1375.4 | Suitable for Use |
| Subaru ATF 5AT, Dex II, AT OIL 5D06, ATF, ATF HP | Suitable for Use |
| Suzuki ATF 2326, 2384K, JWS 3309, 3314, AT OIL 5D06, ATF 2326, ATF 2384K, 3317 | Suitable for Use |
| Texaco 7045-E, 8072B, N402 | Suitable for Use |
| Toyota D-II, D-III, Hybrid, T-II, T-III, T-IV, WS | Suitable for Use |
| Type A | Suitable for Use |
| Vickers M-2950-S, I-286-S | Suitable for Use |
| Voith 55.6335 (G607), Svc Bltn #013 and #118 | Suitable for Use |
| Volvo 97325, 97335, CE 97340, 1161521, 1161621, 1161540, 1161640, 31256774, 31256675 | Suitable for Use |
| Volvo P/N 1161540-8 | Suitable for Use |
| Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342 | Suitable for Use |
| VW 5 HP ZF5 HP 30, 18FL, 30, 19FL, 24A, G-055-025 A2, G-055-540, G-055-162 (ZF Lifeguardfluid 5), G-055-162-A2, -A6 (ZF Lifeguardfluid 6 Plus), G-060-162 (ZF Lifeguardfluid 8), G US 000 162, TL 521 62, TL 521 62, TL 52540 A, VW G 052 162, 052 162 A1 A2 A6, 099, VW TL52162 (LT71141) | Suitable for Use |
| Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-389 | Suitable for Use |
| ZF all 3 & 4 speed trans., 8 speed trans., 9 speed trans., ZF TE-ML 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 14C, 16L, 17C, 21L | Suitable for Use |