



MAXPAR® TW 70I

TECHNICAL WHITE MINERAL OIL

Analysis	Test Method	Typical Values	Standard CoA
Appearance	Visual	Clear & Bright	–
Viscosity, SUS @ 100°F	ASTM D2161	70	✓
Viscosity, cSt @ 40°C	ASTM D7042	12.3	✓
Gravity, API	ASTM D4052	34.7	✓
Specific Gravity, 60/60°F	ASTM D4052	0.8514	✓
Density, lb/gal @ 60°F	–	7.10	✓
Color, Saybolt	ASTM D156	+30	✓
Flash Point (COC), °F (°C)	ASTM D92	355 (179)	✓
Pour Point, °F (°C)	ASTM D5950	-20 (-28)	✓
FDA 21 CFR 178.3620(b) and 178.3620(c)	ASTM D2269	PASS	✓

PRODUCT NOTES:

- This product contains less than 20 ppm dl-alpha tocopherol (Vitamin E).
- This product meets the requirements of FDA 21 CFR 178.3620(b) and (c) for indirect use in food; FDA 21 CFR 573.680 for use in animal feed; and FDA 21 CFR 175.105, 176.170, 175.230, and 175.300.

CAS No. 8042-47-5 : Mineral oil

RESOLUTE OIL

1-866-690-0417 | 102 Magellan Circle Ste B, Webster, TX 77598 | hello@resoluteoil.com

Product Bulletin / Revision 2022-05-09